



HPC-99 is a matchless heat proof compound which wonderfully works on masonry surface. It stops heat penetration and keeps cool by reflecting more than 90% heat of the sun from surface. It makes you comfortable to walk on, to live with and to save electric energy. It keeps water cool in any type of water storage tank.

Multiple Advantage

- ♦ Very low heat penetration. ♦ Very high heat reflection. ♦ Considerable decrease in room temperature and electrical consumption. ♦ Excellent adhesion to most building materials and no need to cure. ♦ Excellent elastomeric and crack bridging capability. ♦ Anti corrosive, protects reinforcement steel and increases life of building. ♦ Anti fungal, Anti Microbial.
- ♦ Economical. ♦ Safe, Eco-friendly, hygienic.



Normal Terrace



Sloping Terrace

How to Use - HPC-99 is single component ready to use compound.

- ♦ Clean the surface from oil, dust, fungus, grass roots, rust & loose material with wire brush. If possible vacuume cleaning is advisable. ♦ Wash the surface with clean water and let it dry. ♦ Repair gaps & cracks of surface with WAC-99 and cement mortar. Cure it as per normal procedure. (Optional : Non-porous surface like Marble, Green or Kota Stones, Vitrified Tiles required two coat of WAC-99 with cement as a primer for longer lasting & water proofing results.) ♦ HPC-99 is very easy to apply. For best result do not dilute it. ♦ Stir well and apply one coat of HPC-99 by painting brush on the (primed) surface. ♦ After 30 min. apply 2nd coat of HPC-99. ♦ If required give 3rd coat. ♦ Coverage two coats 25-30 sq. ft. /Kg.
- ♦ Wash brush immediately after each use.

Area of Application

- ♦ New & old Terrace : Cement Concrete, Asbestos, Plastic, Wood, Steel, Aluminium or any metals.
- ♦ Exterior Wall : Brick wall with or without plaster. ♦ Terrace Seimming Pool, Water tank, parapet wall, pantry etc. ♦ Cinema hall, Cold Storage. ♦ Staircase, path of Temple. ♦ Pavement, Bridge, Deck, Parking area, Army Baroque, Walking track etc.



Metal Sheet



Plastic Tank

Available Packing : 100 g., 1 kg., 5 kg., 10 kg., 25 kg., 55 kg., 235 kg.